

9/21/22

SAFETY DATA SHEET

According to Regulation (EC) No 1907/2006 (REACH)

1. PRODUCT IDENTIFICATION

Trade Name(s): XT5 RG
Product Description: Coating

Synonyms: N/A CAS No: N/A

Supplier:

EPRO Services, Inc. PO Box 347

Derby, KS 67037

800-882-1896 (8:00am - 5:00pm CST)

2. HAZARD(S) IDENTIFICATION

Physical hazards

Flammable liquids: Category 3

Health hazards

Skin Corrosion/irritation: Category 2

Serious eye damage/eye irritation: Category 2A

Germ cell mutagenicity: Category 1B

Specific target organ toxicity, repeated exposure: Category 2

Aspiration hazard: Category 1

Environmental hazards: Not classified. **OSHA defined hazards:** Not classified.

Label elements







Signal word: Danger

Hazard statement: Flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause genetic defects. May cause damage to organs through prolonged or repeated exposure.

Precautionary statement

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not breathe mist/vapors. Wear protective gloves/protective clothing/eye protection/face protection.

Response: If swallowed: Immediately call a poison center/doctor. Do not induce vomiting. If on skin or hair: Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. In case of fire, use appropriate media to extinguish.

Storage: Store in a well-ventilated place. Keep cool.

Disposal: Not available.

Hazards not otherwise classified (HNOC): None know.

Supplemental information: 84.21% of the mixture consists of components of unknown acute oral toxicity. 99.01% of the mixture consists of components of unknown acute dermal toxicity. 75.3% of the mixture consists of components of unknown acute inhalation toxicity. 90.04% of the mixture consists of components of unknown acute hazards to the aquatic environment. 90.04% of the mixture consists of components of unknown long-term hazards to the aquatic environment.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

 Chemical Name
 CAS No.
 %

 Distillates (petroleum), Hydrotreated Light
 64742-47-8
 5 - < 10</td>

 Oleylamine
 112-90-3
 1 - < 3</td>

4. FIRST-AID MEASURES

Inhalation: Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact: Remove contaminated clothing immediately. Rinse skin with water/shower. Get medical attention if irritation develops and persists. Wash contaminated clothing before reuse.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develop and persists.

Ingestion: Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and delayed: Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed: Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

General information: Take off all contaminated clothing immediately. If exposed or concerned, get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the materials involved and take precautions to protect themselves. Show this SDS to the doctor in attendance. Wash contaminated clothing before reuse.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media: Water fog. Foam. Carbon dioxide (CO2). Dry chemical powder.

Unsuitable extinguishing media: Do not use water jet as an extinguisher as this will spread the fire.

Specific hazards arising from the chemical: Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Firefighting equipment/instructions: In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods: Use standard firefighting procedures and consider the hazards of other involved materials. **General fire hazards:** Flammable liquid and vapor.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures: Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breath mist or vapor. Do not touch damaged container or spilled material unless wearing appropriate protective clothing. Ventilate closed space before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection see section 8 of the SDS.

Methods and materials for containment and cleaning up: Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures again static discharge. Use only non-sparking tools. Large spills: Stop the flow of material if this is without risk. Dike the spilled material where possible. Use a non-combustible material like vermiculite, dry sand, or earth to soak up product and place into containers for later disposal. Following product recovery, flush area with water. Small spills: Absorb with earth, sand, or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for reuse. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS. Environmental precautions: Avoid discharge into drains, water courses, or onto the ground.

7. HANDLING AND STORAGE

Precautions for safe handling: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store, or open near an open flame, sources of heat or source of ignition. Protect material from direct sunlight. When using do not smoke. Take precautionary measure against static discharges. Do not breathe mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities: Store locked up. Keep away from heat, sparks, and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of SDS).

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	<u>Value</u>
Distillates (petroleum), Hydrotreated Light	PEL	400 mg/m3
(CAS 64742-47-8)		100 ppm

US NIOSH: Pocket Guide to Chemical Hazards

ComponentsTypeValueDistillates (petroleum), Hydrotreated LightTWA100 mg/m3(CAS 64742-47-8)

Biological limit values: No biological exposure limits noted for the ingredients.

Appropriate engineering controls: Good general ventilation should be used (see CIM IG-9 for additional details). Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin protection – hand: Wear appropriate chemical resistant gloves. **Skin protection – other:** Wear appropriate chemical resistant clothing.

Respiratory protection: If engineering controls do not maintain airborne concentrations below

recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

Thermal hazards: Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations: Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid

Odor: Mild. Hydrocarbon-like

pH: Not available

Initial boiling point & range: 347°F (175°C) est

Evaporation rate: Not available
Flammability limit-lower %: 0.7% est
Explosive limit-lower %: 0.7% est
Vapor pressure: 3 mm Hg est
Relative density: Not available

Partition coefficient (n-octanol/water): Not available

Decomposition temperature: Not available

Density: 0.90 g/cm3

Flammability class: Combustible II est

VOC: 0.8 – 0.98 g/l

Color: Black

Odor threshold: Not available

Melting/freezing point: Not available

Flash point: 101°F (38.3°C)

Flammability (solid, gas): Not available Flammability limit-upper %: 5% est Explosive limit-upper %: 5% est

Vapor density: 4.9

Solubility (water): Not available

Auto-ignition temperature: 410°F (> 210°C) est

Viscosity: 3500 - 6500 cP

Explosive properties: Not explosive **Oxidizing properties:** Not oxidizing

10. STABILITY AND REACTIVITY

Reactivity: The product is stable and non-reactive under normal condition of use, storage, and transport.

Chemical stability: Material is stable under normal conditions.

Possibility of hazardous reactions: No dangerous reaction known under conditions of normal use.

Conditions to avoid: Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources.

Avoid temperature exceeding the flash point. Contact with incompatible materials.

Incompatible materials: Strong oxidizing agents.

Hazardous decomposition products: No hazardous decomposition products are known.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation: Prolonged inhalation may be harmful.

Skin contact: Causes skin irritation.

Eye contact: Causes serious eye irritation.

Ingestion: Droplets of product aspirated into lungs through ingestion or vomiting may cause a serious chemical

pneumonia.

Symptoms related to the physical, chemical, and toxicological characteristics: Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity: May be fatal if swallowed and enters airways.

Product Species Test Results

XT5 RG

Acute Inhalation

LC50 Rat 612 mg/l, 4 hrs

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization: Not a respiratory sensitizer. **Skin sensitization:** Not expected to cause skin sensitization.

Germ cell mutagenicity: May cause genetic defects.

Carcinogenicity: Not classifiable as to carcinogenicity to humans. **IARC Monographs. Overall Evaluation of Carcinogenicity:** Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052): Not listed. US. National Toxicology Program (NTP) Report on Carcinogens: Not listed.

Reproductive toxicity: This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure: Not classified.

Specific target organ toxicity – repeated exposure: May cause damage to organs through prolonged or

repeated exposure.

Aspiration hazard: May be fatal if swallowed and enters airways.

Chronic effects: Prolonged inhalation may be harmful. May cause damage to organs through prolonged or

repeated exposure.

12. ECOLOGICAL INFORMATION (non-mandatory)

Ecotoxicity: The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

<u>Product</u>	<u>Species</u>	Test Results
XT5 RG		
<u>Aquatic</u>		
Crustacea EC50	Daphnia	37.6506 mg/l, 48 hrs
Fish LC50	Fish	29.1165 mg/l, 96 hrs
<u>Acute</u>		
Crustacea EC50	Daphnia	27.1084 mg/l, 48 hrs est.
Fish LC50	Fish	22.0884 mg/l, 4 days est.

<u>Components</u> <u>Species</u> <u>Test Results</u>

Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)

<u>Aquatic</u>

Crustacea EC50 Water flea (Daphnia pulex) >= 2.7 - <= 5.1 mg/l, 48 hrs

<u>Acute</u>

Crustacea EC50 Water flea (Daphnia pulex) >= 2.7 - <= 5.1 mg/l, 48 hrs

Fish LC50 Bluegill (Lepomis macrochirus) 2.2 mg/l, 4 days

Persistence and degradability: No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential: No data available.

Mobility in soil: No data available.

Other adverse effects: No other adverse environmental effect (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. DISPOSAL CONSIDERATIONS (non-mandatory)

Disposal instructions: Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations: Dispose in accordance with all applicable regulations.

Hazardous waste code: D001: Waste flammable material with a flash point <140°F. Waste code should be assigned in discussion between user, producer, and waste disposal company.

Waste from residues / unused products: Dispose of in accordance with local regulations. Empty containers or liner may retain some product residues. This material and its container must be disposed of in a safe manner (see Disposal instructions).

Contaminated packaging: Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty container should be taken to an approved waste handling site for recycling or disposal.

14. TRANSPORT INFORMATION (non-mandatory)

DOT: Not regulated as dangerous goods. This material can be reclassified as non-hazardous for DOT Transportation per 49 CFR 173.150 (f). This material can also be shipped as UN1139 Coating Solutions, Class 3, PGIII.

IATA

UN number: UN1139

UN proper shipping name: Coating solution (include surface treatments or coatings used for industrial or

other purposes such as vehicle undercoating, drum, or barrel lining).

Transport hazard classes

Class: 3

Subsidiary risk: - Packing group: |||

Environmental hazards: No

ERG Code: 3L

Special precautions for user: Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo aircraft: Allowed with restrictions.

Cargo aircraft only: Allowed with restrictions.

IMDG

US number: UN1139

UN proper shipping name: Coating Solution (includes surface treatments or coatings used for industrial

Purposes such as vehicle under-coating, drum, or barrel lining). (

Transport hazard classes

Class: 3

Subsidiary risk: Packing group: |||
Environmental hazards
Marine pollutant: No

EmS: F-E, S-E

Special precautions for user: Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPO 73/78 and the IBC Code: Not established.

IATA; IMDG



15. REGULATORY INFORMATION (non-mandatory)

US federal regulations: This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D): Not regulated.

CERLA Hazardous Substance List (40 CFR 302.4): Not listed. **SARA 304 Emergency release notification:** Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053): Not listed.

Superfund Amendment and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance: Not listed.

SARA 311/312 Hazardous chemical: Yes

Classified hazard categories: Flammable (gases, aerosols, liquids, or solids). Skin corrosion or irritation. Serious eye damage or eye irritation. Germ cell mutagenicity. Specific target organ toxicity (single or repeated exposures). Aspiration hazard.

SARA 313 (TRI reporting): Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List: Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130): Not regulated.

Safe Drinking Water Act (SDWA): Not regulated.

US state regulations

US California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a): Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8).

California Proposition 65: California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65). This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

International Inventories

Country or region	Inventory Name	On Inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Exiting Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Exiting and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS) Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
US & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*&}quot;Yes" indicates that all components of this product comply with the inventory requirements by the governing countries. "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country.

16. OTHER INFORMATION

HMIS ratings

Health: 3 Flammability: 3 Physical hazard: 0

NFPA ratings Health: 2

Flammability: 3 Instability: 0

This information provided on this Safety Data Sheet is correct to the best of our knowledge, information, and belief at the date of its publication, however, no guarantee is made to its accuracy. The information given is designated only as a guide for safe handling, use, processing, storage, transportation, disposal, and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process. This material is intended for industrial use only. No warranty, expressed or implied, is made.