

- 1. CRACKS GREATER THAN 1/4" MUST BE ROUTED OUT AND TREATED LIKE A JOINT.
- 2. XT5 IS NOT RATED FOR LONG TERM UV EXPOSURE AND MUST BE PROTECTED WITH BACKFILL, CONCRETE, OR WITHIN AN ENCLOSED TANK.
- 3. FOR LONG TERM UV EXPOSURE, SEE XT1.

G:\.shortcut-targets-by-id\0B1j3RtmQZ-btQUNqNGJPcEc0Z1k\Epro Master Folder\Drafting\Details\Walls\XT5\24.252.3 WALL CRACK AND JOINT TREATMENT - PLAN VIEW - STATIC - 1\_8 1 4 INCH.dwg [Detail] September 29, 2022 - 11:43am

## WALL CRACK AND JOINT TREATMENT - PLAN VIEW - STATIC - (1/8" - 1/4")



STSTEWNAME	DIVAWING NOMBER
XT5	24.252.3
DRAFTER	DATE
RJT	09/26/2022



AS A SUPPLIER OF FINISHED RPODUCTS ONLY, EPRO SERVICES, INC. DOES NOT ASSUME RESPONSIBILITY FOR ERRORS IN DESIGN, ENGINEERING OR DIMENSIONS. THE PROJECT TEAM MUST VERIFY ALL DIMENSIONS AND SUITABILITY OF DETAILS. THE PRODUCTS LISTED ARE TRADEMARKS OF EPRO SERVICES, INC.

**NTS** 

PAGE <u>1</u> OF <u>1</u>