

Product Description

Basic Use: e.tape is designed to act as a seam splice when used to seam e.shield geomembrane.

Composition: e.tape is a 7.0 mil polyethylene backed, synthetic rubber adhesive coated heavy-duty adhesive tape.

Benefits

- Permanently tacky adhesive bonds well to most surfaces over a wide temperature range.
- Excellent low-temperature bonding.
- Conforms well to irregular surfaces
- Maintains a watertight seal in all weather conditions
- Good tear characteristics.

Limitations

 Not to be used when elongation and movement is not desired.

Technical Data

Properties: See physical properties table.

Specification Writer: Contact EPRO before writing specifications on this product. E.Series system assemblies should be reviewed in order to meet project specific site conditions.

Installation

Application: Please refer to manufacturer's specifications.

Availability and Packaging

Contact EPRO sales representative for local distributors or authorized applicators (www.eproinc.com).

Technical Services and Information

Complete technical services and information are available by contacting EPRO at 800.882.1896 or www.eproinc.com.

Typical Physical Properties

Physical Property	Value
Adhesive Thickness	2.5 mils
Total Thickness	7.0 mils
Backing Adhesion	35 oz./in.
Elongation	80%
Peel Adhesion to Stainless Steel	60 oz./in.
Tensile Strength (ASTM D1000)	18 lbs./in.

Warranty

Limited Warranty: EPRO Services, Inc. believes to the best of its knowledge that performance tables are accurate and reliable. EPRO warrants this product to be free from defects. EPRO makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of MERCHANTABILITY OR FITNESS FOR PARTICULAR PURPOSE. EPRO's liability shall be limited in all events to supplying sufficient product to retreat the specific areas to which defective product has been applied. EPRO shall have no other liability, including liability for incidental or resultant damages, whether due to breach of warranty or negligence. This warranty may not be modified or extended by representatives of EPRO or its distributors.

